

**tyco**



**OVER 110 YEARS OF QUALITY & SERVICE IN THE HOSE INDUSTRY**

**MANUFACTURER OF MUNICIPAL, FORESTRY AND INDUSTRIAL HOSE**

# ECONOFLO™



NIEDNER IS AN ISO9001:2000 CERTIFIED COMPANY BY UL REGISTRAR  
SUPERIOR PRODUCTS THAT SUPPORT YOU IN **SAVING LIVES**

[www.niedner.com](http://www.niedner.com)

# ECONOFLO™

Lightweight and compact, ECONOFLO™ has standard brass GHT fittings, and is factory proof pressure test rated at 300 PSIG (2100 kPa). A 100% filament polyester, elastomer lined, single-jacket flat-woven hose; available in 3/4" and 5/8" (16 and 19 mm) sizes with yellow ENCAP™ or untreated. Designed for Wildland applications, ECONOFLO™ can also be used for Hazardous Material operations and personnel decontamination. When used on or around asphalt or pavement, care must be taken to minimize damage by abrasion or pin-holing may occur. ECONOFLO™ options include a Pouch for belt wear and a compact Brass Nozzle. Its variety of exceptional features makes ECONOFLO™ a very popular hose.

Construction: Circular woven, single jacket 100% virgin spun polyester.  
 Tube: Extruded T.P.U. elastomer - Ozone and age resistant.  
 Standard Lengths: 50' and 100' (15,2 and 30,5 m)  
 Available Options: Pouch and/or brass nozzle. ENCAP™ encapsulation (yellow) provides water repellency, abrasion, oil and chemical resistance.

## How to specify ECONOFLO™

- The hose shall be a single jacket construction with 100% spun polyester yarn.
- There shall be a minimum of 21 filler yarns per inch in the jacket.
- The thickness of the lining shall be 0.012" (305 µm) minimum and it shall be constructed of extruded T.P.U. elastomer.
- If required (optional) the outside jacket shall be treated with yellow ENCAP™ elastomer, which shall completely encapsulate the jacket fibers and not merely surface coat the jacket.
- The hose service temperature range shall be -60°F to 140°F (-51°C to 60°C).
- At 300 PSIG (2100 kPa), its elongation shall not exceed 2% of the initial hose length, it shall not warp more than 10 inches (25 cm) and should not rise from the test table.
- The hose shall not twist more than 5 turns per 50 ft (15,2 m) while at 300 PSIG (2100 kPa).
- Minimum service test pressure of 150 PSIG (1050 kPa).
- Minimum proof test pressure of 300 PSIG (2100 kPa).
- Minimum straight burst test pressure of 600 PSIG (4200 kPa).
- The hose while curved to a radius of 27" (69 cm) shall not burst at less than 600 PSIG (4200 kPa).

## ECONOFLO™ PHYSICAL PROPERTIES

Hose size	Spec number	Coupling bowl size	Weight / 50 ft (15,2 m) coupled	Coil dia. / 50 ft (15,2 m)
5/8 " (16 mm)	2463	5/8" GHT (15,9 mm)	1.0 lbs (0,5 kg)	9.0 " (23 cm)
3/4 " (19 mm)	2475	3/4" GHT (19,1 mm)	1.5 lbs (0,7kg)	9.0 " (23 cm)

For more information please call your authorized dealer.

**NIEDNER**  
 ISO 9001 REGISTERED

**1-800-567-2703**  
 sales.niedner@tycoint.com



**NIEDNER**  
 675 Merrill St. Coaticook, QC Canada J1A 2S2  
 PO Box 38, Norton, VT USA 05907  
 Tel.: (819) 849-2751 1-800-567-2703 Fax.: (819) 849-7539 E-mail: sales.niedner@tycoint.com Web: www.niedner.com