



OVER 110 YEARS OF QUALITY & SERVICE IN THE HOSE INDUSTRY

MANUFACTURER OF MUNICIPAL, FORESTRY AND INDUSTRIAL HOSE

POWERLINE®



NIEDNER IS AN ISO9001:2000 CERTIFIED COMPANY BY UL REGISTRAR

SUPERIOR PRODUCTS THAT SUPPORT YOU IN **SAVING LIVES**

(800) 567-2703

www.niedner.com

MUNICIPAL FIRE HOSE

POWERLINE®

A unique fire hose designed by firefighters for maximum performance and dependability, POWERLINE® is a 100% polyester double jacket, 400 PSIG (2800 kPa) service test pressure rated fire hose, with an EPDM rubber liner. The outer jacket of spun polyester is constructed using a patented polymeric infusion process that produces superior kink resistance and water flow. Patent No. 6336473 applies. While lighter in weight than most of its competitors, POWERLINE® is resistant to cuts, snags, punctures, and abrasion. This unique product is being widely used in extreme attack hose applications. The bright yellow ENCAP™ outer jacket with blue woven stripe enhances the visibility of this hose in all conditions. Test POWERLINE® and convince your fire department of its value.

Construction: Circular woven, double jacket 100% virgin spun polyester.
Tube: Lightweight extruded E.P.D.M. rubber - Ozone and age resistant.
Standard Lengths: 50' and 100' (15,2 and 30,5 m)

How to specify POWERLINE®

- The hose shall be of double jacket construction with 100% spun polyester yarn in both jackets.
- There shall be a minimum of 10.0 filler yarns per inch.
- The thickness of the lining shall be 0.022" (559 µm) minimum and it shall be constructed of lightweight extruded E.P.D.M. rubber.
- The outside jacket shall be treated with ENCAP™ elastomer, which shall completely encapsulate the jacket fibers and not merely surface coat the jacket. It shall have a blue 3/4" wide stripe woven into it.
- The hose service temperature range shall be -40°F to 175°F (-40°C to 79°C).
- FM abrasion test of 30,000 cycles minimum and Taber abrasion test of 15,000 cycles minimum.
- At 800 PSIG (5600 kPa), its elongation shall not exceed 10% of the initial hose length, it shall not warp more than 20 inches (51 cm) and should not rise from the test table.
- The hose shall not twist more than 3 turns per 50 ft (15,2 m) while at 800 PSIG (5600 kPa).
- Minimum service test pressure of 400 PSIG (2800 kPa).
- Minimum proof test pressure of 800 PSIG (5600 kPa).
- Minimum straight burst test pressure of 1200 PSIG (8400 kPa).
- The hose while curved to a radius of 27" (69 cm) shall not burst at less than 1200 PSIG (8400 kPa).
- Meets or exceeds NFPA 1961 specifications.

POWERLINE® PHYSICAL PROPERTIES

Hose size	Spec number	Coupling bowl size	Weight / 50 ft (15,2 m) uncoupled	Coil dia. / 50 ft (15,2 m)	Minimum kink burst test pressure
1 1/2" (38 mm)	4665	1 15/16" (49,2 mm)	16.0 lbs (7,3 kg)	16" (41 cm)	900 PSIG (6300 kPa)
1 3/4" (45 mm)	4667	2 1/16" (52,4 mm)	18.5 lbs (8,4 kg)	16" (41 cm)	900 PSIG (6300 kPa)

For more information please call your authorized dealer.



1-800-567-2703
 sales.niedner@tycoint.com



Tel.: (819) 849-2751
 1-800-567-2703
 Fax.: (819) 849-7539

675 Merrill St. Coaticook, QC Canada J1A 2S2
 E-mail: sales.niedner@tycoint.com
 Web: www.niedner.com

