



SNOW HOSE™



- Designed for rugged conditions and very demanding environments.
- 100% polyester double jacketed hose.

- Flexible & easy to roll.
- Long lasting, dependable and very high safety rating



SNOW HOSE™

Ski hills recognize Niedner's Snow Hose products are specifically produced to meet the unique and demanding requirements found on ski slopes. This Snow Hose is a durable, high performance and compact product designed to meet the demands of snowmakers. SNOW HOSE™ comes with a standard high visibility yellow ENCAP™ treatment for added safety, abrasion resistance, and also minimizes snow adhesion. It is flexible to -60°F (-51°C), and the tight weave of the outer jacket resists cutting and punctures.

The three different grades Niedner provides give snowmakers the opportunity to choose the right hose for their specific application needs.

Construction: Circular woven, double jacket 100% virgin spun polyester.
Tube: Extruded T.P.U. elastomer - Ozone and age resistant.
Standard Lengths: 50' and 100' (15,2 and 30,5 m)
Color option: Available in orange, red or green with a minimum order of 2000 feet (609,6 m) per color, per order.

How to specify SNOW HOSE™

- Remains flexible down to -60°F (-51°C).
- TPU liner provides superior ozone and age resistance over rubber liner with much thinner wall surface which makes the hose lighter and easier to handle with less bulk.
- All lengths are factory tested with the couplings attached.
- Double jacket construction provides maximum durability under harsh conditions.
- All types require thin wall double jacket tail gaskets in the couplings.

The Economizer: A utility Snow Hose designed for everyday use.

SNOW HOSE™ 1200 SERIES, PHYSICAL PROPERTIES						
Hose size	Spec number	Coupling bowl size	Weight / 50 ft (15,2 m) uncoupled	Service test press	Proof press.	Burst press.
1 1/2" (38 mm)	10015	1 15/16" (49,2 mm)	10.5 lbs 4,8 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1200 PSI 8400 kPa
2 (51 mm)	10020	2 5/16" (58,7 mm)	14.0 lbs (6,4 kg)	400 PSI 2800 kPa	800 PSI 5600 kPa	1200 PSI 8400 kPa
2 1/2" (64 mm)	10025	3.0" (72,6 mm)	18.0 lbs 8,2 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1200 PSI 8400 kPa

*The Champion - Flexible - Lightweight - Highly Visible
 Designed for hills requiring a more flexible product in a moderately demanding environment.*

SNOW HOSE™ 1400 SERIES, PHYSICAL PROPERTIES						
Hose size	Spec number	Coupling bowl size	Weight / 50 ft (15,2 m) uncoupled	Service test press	Proof press.	Burst press.
1 1/2" (38 mm)	10115	1 15/16" (49,2 mm)	12.5 lbs 5,7 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1400 PSI 9800 kPa
2" (51 mm)	10120	2 5/16" (58,7 mm)	17.0 lbs 7,7 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1400 PSI 9800 kPa

The Best - Durable - Dependable - Long Lasting Designed for high pressure use under rugged conditions when either snagging, cutting or abrasion are of a major concern.

SNOW HOSE™ 2000 SERIES, PHYSICAL PROPERTIES						
Hose size	Spec number	Coupling bowl size	Weight / 50 ft (15,2 m) uncoupled	Service test press	Proof press.	Burst press.
1 1/2" (38 mm)	10065	1 15/16" (49,2 mm)	16 lbs 7,3 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1800 PSI 12400 kPa
2 (51 mm)	10070	2 3/8" (59,8 mm)	21 lbs 9,5 kg	400 PSI 2800 kPa	800 PSI 5600 kPa	1800 PSI 12400 kPa



1-800-567-2703
 sales@niedner.com

www.niedner.com